

Kanada Standardı Anma Adı	A1/S1A (Al/Ç) mm²	Kesit				Tel Sayıları ve Çapları				Eşdeğer Bakır Kesiti mm²	Anma Çapı	
		AWG veya cir.mils	Al mm²	Çelik mm²	Toplam İletken mm²	Alüminyum		Çelik			Çelik mm	İletken mm
							Çap mm		Çap mm			
SWALLOW	27/4	3	26,69	4,45	31,14	6	2,38	1	2,38	16,78	2,38	7,14
SPARROW	34/6	2	33,59	5,60	39,19	6	2,67	1	2,67	21,09	2,67	8,01
ROBINONE	45/7	88 220	44,70	7,45	52,15	6	3,08	1	3,08	28,11	3,08	9,24
RAVEN	54/9	1/0	53,52	8,92	62,44	6	3,37	1	3,37	33,73	3,37	10,11
PIGEON	85/14	3/0	85,13	14,18	99,30	6	4,25	1	4,25	53,52	4,25	12,75
PARTRIDGE	135/22	266 800	134,87	21,99	156,86	26	2,57	7	2,00	85,17	6,00	16,28
OSTRICH	152/25	300 000	152,19	24,71	176,90	26	2,73	7	2,12	95,60	6,36	17,28
HAWK	242/39	477 000	241,65	39,19	280,84	26	3,44	7	2,67	152,00	8,01	21,77
DRAKE	403/65	795 000	402,56	65,44	468,00	26	4,44	7	3,45	253,30	10,35	28,11
CONDOR	402/52	795 000	402,33	53,15	454,48	54	3,08	7	3,08	253,30	9,24	27,72
RAIL	483/34	954 000	483,40	33,60	517,00	45	3,70	7	2,47	300,00	7,40	29,60
CARDINAL	485/63	954 000	484,53	62,81	547,34	54	3,38	7	3,38	304,00	10,14	30,42
PHEASANT	645/82	1 272 000	645,08	81,71	726,79	54	3,90	19	2,34	405,70	11,70	35,10

Kanada Standardı	Kesit			Anma Kopma	+ 20 °C DC Direnci	Anma Birim Ağırlığı	Standard Ambalaj (Bir Marka Üzerinde)			Akım Taşıma Kapasitesi		
	A1/S1A	AWG	Toplam				İletken	Net	Makara	AMPER		
	(Al/Ç)	veya	İletken									
Anma Adı	mm ²	cir.mils	mm ²	Yükü kg	Ohm/km	kg/km	Adet x Boy m	Ağırlık kg	Tipi	(1)	(2)	(3)
SWALLOW	27/4	3	31,14	1038	1,0742	107,8	2x3200	690	TA	120	160	180
SPARROW	34/6	2	39,19	1290	0,8543	135,7	3x1600	655	TA	140	180	200
ROBINONE	45/7	88 220	52,15	1650	0,6410	179,3	2x1600	575	TA	175	200	230
RAVEN	54/9	1/0	62,44	1969	0,5362	216,2	1x3200	690	TA	195	230	280
PIGEON	85/14	3/0	99,30	2995	0,3366	343,9	1x1800	620	TA	275	300	360
PARTRIDGE	135/22	266 800	156,86	5113	0,2140	543,8	1x1600	880	D	345	460	510
OSTRICH	152/25	300 000	176,90	5755	0,1897	612,9	1x1600	980	EH	410	490	540
HAWK	242/39	477 000	280,84	8798	0,1194	972,8	1x1600	1560	EH	540	670	740
DRAKE	403/65	795 000	468,00	14165	0,0715	1621,9	1x2200	3570	GR	760	900	1020
CONDOR	402/52	795 000	454,48	13003	0,0718	1519,7	1x1600	2450	GR	760	900	1020
RAIL	483/34	954 000	517,00	11864	0,0599	1600,2	1x2000	3200	GR	860	1010	1100
CARDINAL	485/63	954 000	547,34	15589	0,0597	1829,8	1x2000	3660	GR	860	1010	1090
PHEASANT	645/82	1 272 000	726,79	19767	0,0449	2423,5	1x1600	3880	GR	1000	1160	1300